



- ① BRASS TERMINAL
- ② MOULDED THERMOPLASTIC
- ③ "ULTRALX" AC90 LS 600V 90°C (CSA 22.2 No. 51-95)
- ④ LOCKNUTLESS BOX CONNECTOR 1/2" K.O.
- ⑤ TAILS WITH STRIPPED ENDS

WHERE "cc" REPRESENTS COLOUR CODE I.E. "BK" IS BLACK  
 WHERE "d" REPRESENTS CERTIFIED WIRING MATERIAL I.E. "A" IS AC90  
 WHERE "l" REPRESENTS LENGTH CODE I.E. "040" IS 04.0 METERS  
 WHERE "w" REPRESENTS NUMBER OF WIRES FROM 3 TO 7

**SYSTEM IS RATED FOR CONNECTION TO A GROUNDED 277/480V OR 347/600V BRANCH CIRCUIT.  
 MANUFACTURED WIRING SYSTEM UTILIZING 12 AWG APPROVED ULTRALX CABLE.  
 INSTALLATION IN ACCORDANCE WITH THE CEC PART I.  
 ACCEPTABLE FOR USE IN ENVIRONMENTAL AIR SPACES OTHER THAN DUCTS OR PLENUMS  
 PER CEC PART I 12-010(3).  
 MEETS OR EXCEEDS: - CSA 22.2 NO. 203.1**



277/480 OR 347/600 Volt 20 Amp

CDN. PATENT - 1219307

U.S. PATENT - 4775802

ITEM	DESCRIPTION	PART#/POSITION	REMARKS
3	BARE	1	GROUND
	BLACK/YELLOW TRACER	2	DEDICATED LINE
	WHITE	3	NEUTRAL
	RED	4	PHASE A
	BLACK	5	PHASE B
	BLUE	6	PHASE C
	WHITE/YELLOW TRACER	7	DEDICATED NEUTRAL



100-5977 HAZELDEAN ROAD, OTTAWA, ONTARIO, CANADA K2S 1B9  
 TELEPHONE (613) 836-0300 FAX (613) 836-0391  
 TOLL-FREE (866) 233-5328 FAX (866) 933-1933  
 e-mail: support@electeonline.com

**OWNERSHIP OF DOCUMENTS**  
 This drawing and accompanying information as instrument of service are the property of **ELECTEC**.  
 Reproduction or use in whole or in part in any form whether the work for which they are presented be executed or not is forbidden without the express written permission of **ELECTEC**.

**STARTER CABLE**

w7FTccllld

DRAWN BY: J.Y.	APPROVED: D.H.	w7FT.2
DATE: 10-DEC-08	SCALE: N.T.S.	